

## Water softening system WEH1500



### Description

The water softening system reduces limescale in commercial dishwashers and optimises the results of washing due to fewer deposits of hardeners on the washed items. Thanks to the softer water, the amount of detergent needed is minimised. An acoustic signal indicates a low level in the salt reservoir.

### Features

- Material: Plastic
- Water intake temperature from: 1 °C
- Water connection: 3/4"
- Colour: Grey
- Important information: -
- Water intake temperature to: 30 °C
- Connection capacity: 1 unit
- Setting possibilities: Water hardness  
Interval  
Time  
Regeneration  
Day of the week  
Flow rate or time period
- Regeneration: Flow rate or time period
- Output capacity: 1,500 litres / day at 10° dH (total hardness)
- Designed for: Commercial dishwashers
- Operating pressure: 2 - 6 bar
- Brine tank salt store: 20 kg

▶ Continue on the next page



▶ Capacity: 1,500 litres / at 10° dH (total hardness)



▶ Cost-effective and environmentally friendly thanks to reduction in required detergent quantity



▶ Reduction in limescale in the appliance and on the washed items through decrease in water hardness



▶ Acoustic signal if salt reservoir fill level is low

## Water softening system WEH1500

- With active carbon: Yes
- Salt consumption: 0.7 kg / regeneration
- Regeneration time: 45 min.
- Digital display: Yes
- Power load: 0,005 kW | 230 V | 50 Hz
- Size: W 260 x D 465 x H 478 mm
- Weight: 8.52 kg

