

Water softening system WEH1350



► Output capacity at 10° d: 1350 litres / day



► Digital display for setting:

- ✓ Water hardness
- ✓ Interval
- ✓ Regeneration
- ✓ Time
- ✓ Language

Description

System protection for dishwashers

Features

- Water intake temperature from: 5 °C
- Water connection: 3/4"
- Material: Plastic
- Water intake temperature to: 40 °C
- Colour: Grey
- Important information: -
- Setting possibilities: Interval
Regeneration
Language
Time
Water hardness
- Connection capacity: 1 unit
- Regeneration: Flow rate or time period
- Output capacity: 1,350 litres / day at 10° d (total hardness)
- Designed for: Commercial dishwashers
- Operating pressure: 1,5 - 6 bar
- Brine tank salt store: 20 kg

► Continue on the next page



Water softening system WEH1350


- With active carbon: No
- Salt consumption: 0.7 kg / regeneration
- Regeneration time: 66 min.
- Digital display: Yes
- Power load: 0,03 kW | 230 V | 50/60 Hz
- Size: W 255 x D 435 x H 480 mm
- Weight: 11.6 kg



Water softening system WEH1350

Add on Products

Connection kit WEH1350



- Water intake temperature: 40 °C
- Set comprises: 1 hose 1/2" for regeneration, length 2 m
1 hose 3/4" for water connection, length 1.5 m
- Material: Plastic (PVC)
- Important information: -
- Size: W 50 x D 2,000 x H 50 mm
- Weight: 0.55 kg

Code-No. 109884
GTIN 4015613630748