

Vacuum packaging machine K 300/60L





Everything under control: The chamber vacuum packaging machine is equipped with a glass lid and a manometer to monitoring underpressure. A clamp bar in the chamber prevents the vacuuming bag from slipping.

Features

- Material lid: Glass
- Power load: 0,35 kW | 230 V | 50 Hz
- Control unit: Electronic
 ON/OFF switch: Yes
 Colour: Silver Black
- Length welding rod: 300 mm
 Vacuum control: Time-controlled
- Functions: Combined vacuuming and sealing
 - Manual sealing Marinating Stainless steel
- Material: Stainless st Plastic
- Important information:
 Chamber dimensions:
 W 305 x D 320 x H 90 mm
- Lighting: Number of welded joints: 2
- ▶ Continue on the next page



- Combined vacuuming and sealing
- Manual sealing
- Marinating



- Vacuuming intensity can be regulated
- Sealing duration can be regulated: 3 9 seconds



- Vacuum pump: 60 L/min. (approx. 4 m^{3 /h)}
- Sealing rod length: 300 mm
- Number of sealing seams: 2
- A clamp bar in the chamber prevents the vacuuming bag from slipping







Vacuum packaging machine K 300/60L

• Vacuum pump:

Vacuuming intensity can be regulated:Welding duration can be regulated:

• Including:

• Properties:

· Control lamp:

• Maximum vacuum:

• Digital display:

• Size:

• Weight:

60 L / min. (approx. 4 m³ / hours)

yes

3 - 9 seconds

30 vacuuming bags (280 x 330 mm) Vacuuming time: 20 - 99 seconds Pressure display via manometer Clip for vacuuming bag

Combined vacuuming and sealing

Sealing Marinating ON/OFF Cancel -900 mbar

W 375 x D 440 x H 271 mm

15.1 kg







Vacuum packaging machine K 300/60L Add on Products



