

## Vacuum packaging machine K 250/150L



### Description

Powerful and solid chamber vacuum machine with intuitive control. Enclosed insert plates achieve height compensation in the chamber as required.

### Features

- Material lid: Plexiglas
- Power load: 0,5 kW | 230 V | 50 Hz
- Control unit: Toggle
- Control lamp: Combined vacuuming and sealing  
ON/OFF
- Digital display: No
- Lighting: No
- ON/OFF switch: Yes
- Colour: Silver
- Number of welded joints: 1
- Properties: -
- Functions: Combined vacuuming and sealing
- Material: Stainless steel  
Plastic
- Important information: -
- Chamber dimensions: W 256 x D 370 x H 125 mm
- Length welding rod: 250 mm

▶ Continue on the next page



▶ Functions: Combined vacuuming and sealing

▶ Vacuum pump: 150 L/min. (approx. 8/9 m<sup>3</sup>/h)

▶ Number of sealing seams: 1

✓ Sealing rod length: 250 mm



▶ Sealing duration can be regulated: 6 levels



▶ 2 insert plates

✓ For height compensation in the chamber

## Vacuum packaging machine K 250/150L

- Vacuum pump: 150 L / min. (8-9 m<sup>3</sup> / hours)
- Vacuum control: -
- Vacuuming intensity can be regulated: No
- Including: 2 insert plates for height compensation (250 x 300 x 17 mm)
- Welding duration can be regulated: 6 levels
- Maximum vacuum: -995 mbar
- Size: W 320 x D 540 x H 265 mm
- Weight: 29 kg



## Vacuum packaging machine K 250/150L

### Add on Products

#### Vacuum bags K1,2L



- Content: 1,2 litre(s)
- Order quantity unit: 1 pack (100 bags)
- Bag size: 160 x 250 mm
- Designed for: Chamber vacuuming units
- Design: Smooth
- Sous-Vide suitable: Yes

Code-No. 300311  
GTIN 4015613610320

#### Ballast

- Size: W 40 x D 120 x H 32 mm
- Weight: 0.51 kg

Code-No.  
GTIN 4015613425733

#### Vacuum sealer roll set 220



- Set comprises: 2 vacuum film rolls
- Width roll: 22 cm
- Important information: -
- Length roll: 5 m
- Sous-Vide suitable: Yes
- Size: W 220 x D 40 x H 40 mm
- Weight: 0.46 kg

Code-No. 300418  
GTIN 4015613474946