



STROMVERSORGUNG/POWER SUPPLY	380-415V 3+N~ 50-60Hz
M = ANSCHLUSSKLEMME/ TERMINAL CLAMP	FV122 6 POLI - 40 A - 450 V
B1 = SCHALTER/SWITCH	49.44015.712 0,1,2,3 16A 250V T150 55.32532.805
S1 = SICHERHEITSTHERM./SAFETY THERM.	T=160°C -17K 400V 30A 55.32524.160 T=135°C -12K 400V 30A
C1 = SCHALTER /SWITCH	OMRON J7KN-22D-10 OMRON J7KN24 ALLEN BRADLEY 100-C16 KF10
MCR = MIKROSCHALTER/MICRO SWITCH	PANASONIC AM51614D53NAT
LV = KONTROLLAME GRÜN/GREEN IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
LR = KONTROLLAME ROT/RED IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
R1,R2,R3 = HEIZKÖRPER/HEATING ELEMENT	3200 watt (3x) 230V 13.9A
KABEL/CABLE	CAVO H05SJ-K Section 2.5 mmq CAVO H05SJ-K Section 1 mmq
KABEL F. KONTROLLLAMPE/CABLE F. IND. LIGHT	—