



Position	300 x 300 PE 11.33454.246
1	430 watt
2	600 watt
3	1000 watt
4	1500 watt
5	2500 watt
6	4000 watt

ALIMENTAZIONE STROMVERSORGUNG/POWER SUPPLY	380-415V 3N~ 50/60Hz
M=MORSETTIERA ANSCHLUSSKLEMME/TERMINAL CLAMP	FV122 6 POLI - 40 A - 450 V
B1,B2,B3,B4 = COMMUTATORE SCHALTER/SWITCH	43.27232.801 7 POS 32A 250V
BF = COMMUTATORE FORNO SCHALTER f. OFEN/SWITCH F. OVEN	49.44215.700+49.21015.705 0,1,2,3 POS 16A 250V T150
S1 = LIMITATORE DI TEMPERATURA SICHERHEITSTHERMOSTAT/SAFETY THERMOSTAT	EGO 55.32574.110 T=360°C -25K 20(4)A 400V
T1 = TERMOSTATO THERMOSTAT/THERMOSTAT	EGO 55.34052.811 16A 250V T150 [60°C - 295°C]
LV = LAMPADA VERDE KONTROLLAME GRÜN/GREEN IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
LR = LAMPADA ROSSA KONTROLLAME ROT/RED IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
LB = LAMPADA BIANCA KONTROLLAME WEIß/WHITE IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
R1,R2,R3,R4,R5,R6 = RESISTENZE HEIZKÖRPER/HEATING ELEMENT	300x300 4000 watt 230V 17.4A
RF1 = RESISTENZE FORNO SUP. HEIZKÖRPER OFEN/OVEN HEATING ELEMENT	3300 watt 230 V 14.5 A
RF2 = RESISTENZE FORNO INF. HEIZKÖRPER OFEN/OVEN HEATING ELEMENT	2300 watt 220 V 10.5 A
CABLAGGIO ANSCHLUSSKABEL/POWER CORD	CAVO H05SJ-K Section 2.5 mm²
CABLAGGIO LAMPADE KABEL F. KONTROLLAMPE/CABLE F. IND. LIGHT	CAVO H05SJ-K Section 0.75 mm²