

Cupboard 600, W1200, 2SID, SS



Description

Features

| Number of intermediate shelves: | 3 |
|---|--|
| Height-adjustable feet: | Yes |
| Available on request: | Special production |
| | The list price corresponds to the next higher standard dimension |
| Type of door: | Sliding door(s) |
| Design intermediate shelf: | Full-surface |
| Intermediate shelf: | yes |
| Material: | Stainless steel |
| Important information: | - |
| Load-bearing capacity per intermediate shelf, | 115 kg |
| max.: | |
| Size inside: | W 1197 x D 520 x H 1730 mm |
| Door hinge side can be changed: | No |
| Height adjustable: | 1990 mm to 2055 mm |
| Delivery state: | Permanently mounted |
| Height-adjustable immediate shelves: | Yes |
| Properties: | Feet in square tubing 40 x 40 mm |

Continue on the next page





Cupboard 600, W1200, 2SID, SS

- Properties:
- Size:
- Weight:

Shelves turned down 40 mm all-round and reinforced with a cross member Scotch-Brite sanding W 1,200 x D 600 x H 2,000 mm 95 kg







Cupboard 600, W1200, 2SID, SS Add on Products

| Stainl.steel polish.spray 500ml can | | Power cleaner F1L, set of 2 | |
|---|--|---|--|
| | Conception Concep | | |
| Content / can:Application: | 500 ml Remove heavy soiling such as grease residue first | Designed for: | Stubborn dirt, especially in kitchens Grill and combi steamer cleaning (without cleaning system) |
| allow them to cool down first: | Do not spray onto hot surfaces | Content:Model: | 2 x 1 litre Liquid |
| Application: | Before use, bring the can to room temperature and shake well | • Ph level: | High concentrate 13,5 |
| | | | |
| | Code-No. 173031 GTIN 4015613360195 | | Code-No. 173078 GTIN 4015613731926 |