

## Cooling top GL3-2001



- ▶ GN capacity:
  - ✓ 9 x 1/3 GN
  - ✓ Max. depth of GN containers: 150 mm
- ▶ GN containers not included in the delivery



### Description

Clean and hygienic – a glass top for germ protection

### Features

- |                                |   |
|--------------------------------|---|
| • Front pane:                  | Turned-down edges   |
| • Power load:                  | 0,194 kW   230 V   50 Hz  |
| • Material:                    | Chrome-nickel steel   |
|                                | Glass   |
| • Including:                   | 4 bars: length 181 mm, width 25 mm<br>9 bars: length 326 mm, width 25 mm<br>1 bar: length 326 mm, width 40 mm |
| • Safety glass:                | Yes   |
| • Important information:       | -   |
| • Type of glass:               | Single glazing  |
| • Size glass superstructure:   | W 1990 x D 390 x H 195 mm   |
| • Temperature range:           | 0 °C to 10 °C   |
| • Control unit:                | Electronic<br>Knob  |
| • Glass top unit design, back: | Open  |
| • Control lamp:                | ON/OFF  |
| • Temperature control:         | Digital   |

▶ Continue on the next page

## Cooling top GL3-2001

- Climate class: N
- Cooling: Static
- Coolant: R290 / 0,033 kg
- Digital display: Yes
- Lighting: -
- Delivery state: Building kit (simple assembly)
- Depth GN container max.: 150 mm
- Automatic defrosting function: Yes
- Drip water evaporation: Yes
- ON/OFF switch: Yes
- Capacity GN: 9 x 1/3 GN
- Properties: Cooling aggregate with cooling tray
- Design: With glass top
- Not included in delivery: GN containers
- Size: W 2,000 x D 450 x H 430 mm
- Weight: 52.6 kg

