

## Deck oven CL6040-1





Baked goods from a traditional bakestone made of fireclay with separately adjustable upper and lower heat. This deck oven has an impressively low temperature loss even with steaming. External steam generation and the firebrick ensure an almost constant temperature in the baking chamber.

#### **Features**

Description

· Material baking chamber: Refractory clay baking stone Stainless steel

• Number of baking chambers:

· Capacity: 1 x 600 x 400 mm 300 °C • Temperature range to: In 1 °C steps · Temperature control: Upper / lower heat · Heating type:

• Upper / lower heat can be controlled separately:

· Heating output: 2,4 kW

Set in the program Steaming: Manual

· Number of programs: 15 pre-installed programs 84 programmable manually adjustable program

· Number of baking phases:

· Time setting: 1 to 99 minutes

Manual baking time extension

▶ Continue on the next page



- 1 baking chamber
- ✓ Capacity: 1 x 600 x 400 mm



- 99 programs
- 6 baking phases
- 5 parameters
- ► Steam generator: External steam box



Automatic switch-on via timer



- Required for appliance operation
  - ✓ Installation kit LBO100
- The appropriate installation kit must be selected for the combined appliance setup.
- Upstream connection of a water softener is always required.
- A pressure reducer is required from a water pressure of 3.5 bar.







## Deck oven CL6040-1

• Automatic switch-on via timer: Yes • Automatic pre-heating: Yes • Automatic cooling: No • USB connection: Yes R3/4" • Water connection: · Water intake temperature: 10 °C to 40 °C • Interior lighting: LED · Control unit: Touch • Display: Date and time

LCD, 7 inches Programs Timer settings CL

Series: CLEquipment connection: 3 NAC

Properties: Programs from other devices can be imported

Programs with all parameters can be copied within the menu

• Including:

• Power load: 4,8 kW | 400 V | 50/60 Hz

Material: Stainless steelShelf height: 140 mm

• Steam generators: External steam-box

Important information:

 A pressure reducer is required from a water pressure of 3,5 bar
 Upstream connection of a water softener is always required

The LBO100 installation kit is required for individual device operation (the corresponding installation kit must be selected for the com-

bined device configuration) 31 / 2022

Estimated delivery time from our warehouse in

Salzkotten, Germany is week:

Steam-box power: 1,5 kWParameters per baking phase: Baking time

Steaming intensity
Top and bottom heat
Vapour extractor
Pre-heating

Oven dimensions: W 680 x D 420 x H 160 mm
 Size: W 980 x D 900 x H 400 mm

• Weight: 98 kg







## **Installation kit LBO100**



• Important information:

Material:

Stainless steel Rubber

Plastic

• Set comprises:

Condensate collection box Condensate hoses Installation materials

Code-No. 117948 GTIN 4015613805139

## Oven gloves 300



• Colour:

• Can be washed:

• Heat resistant to: 250 °C

• Length:

300 mm Properties: With flame protection

With hanger

Black

No

Fabric density: 640 g/m<sup>2</sup>

## Oven gloves 370



• Properties:

· Colour:

With flame protection

With hanger

Fabric density: 640 g/m<sup>2</sup>

Black No

• Can be washed:

250 °C • Heat resistant to:

· Length: 370 mm

Code-No. A500511 GTIN 4015613735474

## Oven gloves 420



• Properties:

With flame protection

With hanger

Fabric density: 640 g/m<sup>2</sup>

• Colour:

Black

• Can be washed:

No

• Heat resistant to:

250 °C

• Length:

420 mm

Code-No. A500512 GTIN 4015613735481



## Oven gloves 600

· Colour:



With flame protection • Properties:

With hanger

Fabric density: 640 g/m<sup>2</sup>

• Can be washed: No

• Heat resistant to: 250 °C

600 mm • Length:

Code-No. A500513

### Power cleaner F1L, set of 2



• Designed for: Stubborn dirt, especially in kitchens

Grill and combi steamer cleaning (without

cleaning system)

• Content: 2 x 1 litre • Model:

Liquid

High concentrate • Ph level:

13,5

Code-No. 173078 GTIN 4015613731926

#### **Intensive power cleaner F1L**



• Order quantity unit:

1 box (6 bottles)

Content: • Model:

6 x 1 litre

• HACCP compliant:

Liquid

• Chlorine-free:

Yes Yes

Phosphate-free:

Designed for:

Use in kitchens and food processing areas

Code-No. 173280 GTIN 4015613761183

#### Stainl.steel polish.spray 500ml can



• Content / can:

• Application:

Remove heavy soiling such as grease residue

Do not spray onto hot surfaces

• allow them to cool down first:

• Application:

Before use, bring the can to room temperature

and shake well

Code-No. 173031 GTIN 4015613360195



### **Installation kit LBO90**



· Set comprises:

Condensate collection box Condensate hoses Installation materials Water drainage hoses Water supply pressure gauge Water supply hoses Vapour extractor

#### Base frame LBO6040-5





- Material:
- · Height-adjustable feet:
- Format drawers:
- Base shelf:
- Number of drawers:
- Important information:

Stainless steel

600 x 400 mm

Designed for: Convection ovens MC, convection ovens HC, deck oven CL6040-1

Code-No. 117930 GTIN 4015613796413

#### Base frame LBO6040-4





- Format drawers:
- Height-adjustable feet:
- Material:
- Number of drawers:
- Base shelf:
- Important information:

600 x 400 mm

Stainless steel

Designed for: Convection ovens MC, convection ovens HC, deck oven CL6040-1

Code-No. 117931 GTIN 4015613769967

#### Base frame LBO6040-3

STAINLESS STEEL



- Format drawers:
- Height-adjustable feet:
- Material:
- Number of drawers:
- Base shelf:
- Important information:

600 x 400 mm

Nο

Stainless steel

Designed for: Convection ovens MC, convection ovens HC, deck oven CL6040-1

Code-No. 117932 GTIN 4015613796420



## **Condensation hood LBO800**



• Number of fan motors:

• Flame protection filter: No

• Number of filters:

0

Material filter:

• ON/OFF switch: • Important information: No

Assembly type:

Top of appliance

Code-No. 117940 GTIN 4015613769974

## Partial desalination system TKD 13400 FB



• Desalination type:

Partial desalination

• Water connection:

3/4"

• Material:

Plastic

• Sampling tap:

Glass-fibre reinforced Yes

• Colour:

Blue

• Important information:

Code-No. 109878 GTIN 4015613681597