

**100085**

Bedienungsanleitung
Thermo-Transportbehälter 20L

D/A/CH

Instruction manual
Thermo transport container 20L

GB/UK

Mode d'emploi
Conteneur isotherme 20L
pour le transport des aliments

F/B/CH

Gebruiksaanwijzing
Thermisch transport container 20L

NL/B

Instrukcja obsługi
Pojemnik termoizolacyjny do transportu 20L

PL

Инструкция по эксплуатации
Термоконтейнер 20L

RUS


Інструкція обслуговування
Термоконтейнер 20L

UA

Technical information:

Name:	<ul style="list-style-type: none">● Thermal transport container, 20L with spout and shield
Art. no.:	<ul style="list-style-type: none">● 100085
Construction:	<ul style="list-style-type: none">● chrome-nickel steel 18/10, brushed● double walls● lid with 4 latches and silicone seal● 1 handle for carrying, 1 side handle for tipping● aeration valve● stackable
Capacity:	<ul style="list-style-type: none">● 20 litres
Dimensions:	<ul style="list-style-type: none">● Ø 420 mm, H 340 mm
Weight:	<ul style="list-style-type: none">● 7.1 kg

The **thermal transport container** is intended for **transport** of both cold and hot liquids and food products.

Diagram of parts

Tips for the user

- Unpack the thermal container and remove all packing material.
- Open the latches and remove the lid from the container.
- **Prior to using and after every use, wash the container and lid thoroughly in warm water with a mild cleaning agent approved for food service applications.**
- Rinse with clean water and leave the unit to dry, or wipe dry with a soft cloth.
- Regularly clean the spout by running a small amount of water with cleaning agent through it, then clean water.
- Always use soft cloths, never use harsh cleaning substances that may scratch the surface.
- The external surface of the transport container may be cleaned using commercially available substances for stainless steel.
- Ensure that the spout is closed and fill the container with cold or hot fluids or food products (max. 20 litres), replace the lid and secure it using the latches to ensure safe transport.
- The double-wall construction ensures proper insulation. Heat loss is approx. 6°C per hour.



The desired amount of liquid as needed can be taken from the container through the spout (press down)

or



from the top, after releasing the latches and removing the lid from the container. The desired amount of liquid or food product can be taken by tipping the container. Use the carrying handle and side handle.

Bartscher GmbH
Franz-Kleine-Str. 28
D-33154 Salzkotten
Germany

phone: +49 (0) 5258 971-0
fax: +49 (0) 5258 971-120